

	Model 700-D	Models 523 & 523A	Models 524 & 525	Model 527
Recommended Use	Used in conjunction with ATS Doppler Flow Phantoms Models 523, 523A, 524, 525 and 527 for precise system evaluation over a wide range of flow velocities.	Quality Assurance: Clinical Performance In-process Manufacturing Teaching Research & Development Final Q.A. Inspection	Quality Assurance: Clinical Performance In-process Manufacturing Teaching Research & Development Final Q.A. Inspection	Quality Assurance: Clinical Performance In-process Manufacturing Teaching Research & Development Final Q.A. Inspection
Test Performed	N/A	Flow Velocity Sensitivity at varying depths Maximum Penetration Location of Flow	Flow Velocity Sensitivity Maximum Penetration Location of Flow Model 525: Demonstration of the effects of stenosis	Flow Velocity Sensitivity at varying depths Maximum Penetration Location of Flow Directional Discrimination
Features	Warranty 3 months Variable speed pump. Flow rates 9.6 - 960 ml/min. Provided with carrying case & 2-Gallons Model 707 Doppler Test Fluid	Lifetime warranty Used in conjunction with Model 700-D pumping system & Model 707 Doppler Test Fluid	Lifetime warranty Used in conjunction with Model 700-D pumping system & Model 707 Doppler Test Fluid	Lifetime warranty Used in conjunction with Model 700-D pumping system & Model 707 Doppler Test Fluid